

**B.E.G.****LUXOMAT®**

## PD3-1C-FC Set 92197-93085

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 85 x 79 mm
- Power consumption: < 0.3 W

### Order data

Designation	Colour	Art.No
PD3-1C-FC	white	92197
Cover ring PD2/PD3 FC		93085

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 85 x 79 mm
Power consumption:	< 0.3 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across
Range:	max. Ø 6 m towards max. Ø 4 m seated
Monitored area (tangential movement):	78 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	<b>jet black glossy, similar to RAL9005 (93085)</b>

## Channel 1 (lighting control)

Switching power:	2000 W, $\cos \varphi$ = 1 1000 VA, $\cos \varphi$ = 0.5 400 W LED, minimum runtime > 5 min max. inrush current $I_p$ (20 ms) = 80 A
Type of contact (k):	µ-contact, NO contact
Follow-up time:	30 sec - 30 min, Pulse
Switch-on threshold:	10 - 2000 Lux

## Product information

Set : PD3-1C-FC + Cover ring PD2/PD3 FC jet black  
glossy, similar to RAL9005



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD3-1C-FC**  
Art.No: 92197

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Ø 85 x 79 mm  
Power consumption: < 0.3 W



**Cover ring PD2/PD3 FC**  
Art.No: 93085

Dimensions: Ø 84 x 9 mm  
Housing: polycarbonate, UV-resistant  
Material color: jet black glossy, similar to RAL9005