

**B.E.G.****LUXOMAT®**

## PD3-1C-SM

Prod.No. 93091 EAN: 4007529930913

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 106 x 53 mm
- Power consumption: < 0.3 W

### Order data

Designation	Colour	Art.No
PD3-1C-SM	black	93091

### Accessories

Designation	Colour	Art.No
Wire basket BSK (Ø 200 x 90 mm)	white	92199

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 106 x 53 mm
Power consumption:	< 0.3 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	
Monitored area (tangential movement):	78 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP44 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	black mat, similar to RAL9005

### Channel 1 (lighting control)

Switching power:	2000 W, $\cos \varphi$ = 1 1000 VA, $\cos \varphi$ = 0.5 400 W LED, minimum runtime > 5 min max. inrush current $I_p$ (20 ms) = 80 A
Type of contact (k):	µ-contact, NO contact
Follow-up time:	30 sec - 30 min, Pulse
Switch-on threshold:	10 - 2000 Lux

## Product information

Ceiling motion detector
One channel for light switching
Zero crossing switching
Switching for all types of light fixtures by high performance relay
Special optical system for detection of even the smallest movements
Serial impulse function



## Accessories



### **Wire basket BSK (Ø 200 x 90 mm)**

Art.No: 92199

Dimensions: Ø 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket