

**B.E.G.**

**LUXOMAT®**



## PD4-M-1C-C-SM Set 92587-92441

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **Ø 101 x 76 mm + 130 x 100 x 53 mm (92441)**
- Power consumption: approx. 0.5 W

### Areas of application

- corridors/hallways

### Order data

Designation	Colour	Art.No
PD4-M-1C-C-SM	white	92587
Wall holder PD4-SM	white	92441

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Ø 101 x 76 mm + 130 x 100 x 53 mm (92441)</b>
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 40 m across max. Ø 20 m towards
Range:	250 m <sup>2</sup> / 2.5 m mounting height
Monitored area (tangential movement):	2.4 m / 2.6 m / 2.5 m
Mounting height min./max./recommended:	IP54 / Class II
Degree / class of protection:	IK04
Impact strength:	-25 °C to +50 °C
Ambient temperature:	polycarbonate, UV-resistant
Housing:	white mat, similar to RAL9010
Material color:	

### Channel 1 (lighting control, potential-free (dry))

Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 800 W LED max. inrush current $I_p$ (20 ms) = 165 A max. inrush current $I_p$ (200 $\mu$ s) = 800 A
Type of contact (k):	1x $\mu$ -contact, dry NO contact with tungsten pre-make contact
Follow-up time:	15 sec - 30 min, Pulse
Switch-on threshold:	10 - 2000 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD4-M-1C-C-SM + Wall holder PD4-SM white

Occupancy detector designed for corridors

One potential-free (dry) switching contact

Version as master device

Detection area can be extended by using slave devices

Manual switching via push-button possible

Additional functions can be set up using the optional remote control.

Factory settings 10 min and 500 lux

There are markings to ensure correct alignment during installation



## Set items

To receive the bundle according to the technical specification, please order the items listed.




### **PD4-M-1C-C-SM**

Art.No: 92587

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 101 x 76 mm

Power consumption: approx. 0.5 W



### **Wall holder PD4-SM**

Art.No: 92441

Dimensions: 130 x 100 x 53 mm

Housing: polycarbonate, UV-resistant

Material color: white