

**B.E.G.****LUXOMAT®**

## PD4-M-1C-FC Set 92585-92992

230V PIR motion detector with 360° detection and a range of up to Ø24m (450 m<sup>2</sup>), remote-controlled

### Order data

Designation	Colour	Art.No
PD4-M-1C-FC	white	92585
Square design frame PD4-FC	pure white	92992

### Areas of application

- open-plan offices
- conference rooms
- classrooms/seminar rooms
- entrance halls
- corridors/hallways
- toilets
- equipment rooms
- small offices

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 97 x 103 mm
Power consumption:	approx. 0.4 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010

### Channel 1 (lighting control, potential-free (dry))

Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 800 W LED max. inrush current $I_p$ (20 ms) = 165 A max. inrush current $I_p$ (200 $\mu$ s) = 800 A
Type of contact (k):	1x $\mu$ -contact, dry NO contact with tungsten pre-make contact
Follow-up time:	15 sec - 30 min, Pulse
Switch-on threshold:	10 - 2000 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD4-M-1C-FC + Square design frame PD4-FC  
pure white mat, similar to RAL9010

Occupancy detector with extended detection area

One potential-free (dry) contact

Version as master device

Detection area can be extended by using slave devices

Manual switching via push-button possible

Additional functions can be set up using the optional remote  
control.

Factory settings 10 min and 500 lux



## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD4-M-1C-FC**  
Art.No: 92585

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Ø 97 x 103 mm  
Power consumption: approx. 0.4 W



**Square design frame PD4-FC**  
Art.No: 92992

Dimensions: 101 x 101 x 11.8 mm  
Housing: polycarbonate, UV-resistant  
Material color: pure white mat, similar to RAL9010