

B.E.G.**LUXOMAT®**

PD4-M-1C-GH-SM Set 92245-92375-92199

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **Ø 200 x 90 mm (92199)**
- Power consumption: approx. 0.5 W

Areas of application

- high-bay warehouse
- sports halls/ storage rooms

Order data

Designation	Colour	Art.No
PD4-M-1C-GH-SM	white	92245
Surface mounting socket IP65 for PD4-SM IP20	white	92375
Wire basket BSK (Ø 200 x 90 mm)	white	92199

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 200 x 90 mm (92199)
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° oval (Ceiling mounting)
Range:	30 m x 19 m
Monitored area (tangential movement):	440 m ² / 14 m mounting height
Mounting height min./max./recommended:	5 m / 16 m / 14 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK09 (92199)
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant + coated steel basket (92199)
Material color:	white mat, similar to RAL9010

Channel 1 (lighting control, potential-free (dry))

Switching power:	2300 W, $\cos \varphi = 1$ 1150 VA, $\cos \varphi = 0.5$ 800 W LED max. inrush current I_p (20 ms) = 165 A max. inrush current I_p (200 μ s) = 800 A
Type of contact (k):	1x μ -contact, dry NO contact with tungsten pre- make contact
Follow-up time:	15 sec - 30 min, Pulse
Switch-on threshold:	20 - 2000 Lux
Light measuring:	Mixed light measuring

Product information

Set : PD4-M-1C-GH-SM + Surface mounting socket
IP65 for PD4-SM IP20 white + Wire basket BSK (Ø
200 x 90 mm) white

Occupancy detector designed for high-bay warehouses

One potential-free (dry) switching contact

Version as master device

Detection area can be extended by using slave devices


Easy operation with remote control (required)

Manual switching via push-button possible

There are markings to ensure correct alignment during
installation

**When used in high-bay warehouses, care should be
taken that, in the cross-aisles of the warehouse,
detectors are installed that can detect movement only
in the desired aisle locations, by using blinds or other
technical arrangements.**

Factory settings 3 min and 1000 lux





Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4-M-1C-GH-SM

Art.No: 92245

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 98 x 63 mm

Power consumption: approx. 0.5 W



Surface mounting socket IP65 for PD4-SM IP20

Art.No: 92375

Dimensions: Ø 115 x 70 mm

Degree / class of protection: IP65

Impact strength: IK07



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket