

**B.E.G.**

**LUXOMAT®**



## PD4-M-TRIO-C-3P-SM Set 92747-92386

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 125 x 85 mm
- Power consumption: approx. 0.5 W

### Order data

Designation	Colour	Art.No
PD4-M-TRIO-C-3P-SM	white	92747
Socket IP54 PD4-TRIO-SM	white	92386

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 125 x 85 mm
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 40 m across
Range:	max. Ø 20 m towards
Monitored area (tangential movement):	250 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection:	<b>IP54 (92386)</b>
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010

### Channel 1 (lighting control, potential-free (dry))

Switching power:	2300 W, cos $\varphi$ = 1 1150 VA, cos $\varphi$ = 0.5 300 W LED
Type of contact (k):	2x $\mu$ -contact, dry Contact NC with tungsten pre-make contact
Follow-up time:	15 sec - 30 min, Pulse
Switch-on threshold:	10 - 2000 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD4-M-TRIO-C-3P-SM + Socket IP54 PD4-TRIO-  
SM white



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD4-M-TRIO-C-3P-SM**

Art.No: 92747

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 125 x 85 mm

Power consumption: approx. 0.5 W



### **Socket IP54 PD4-TRIO-SM**

Art.No: 92386

Degree / class of protection: IP54

Housing: polycarbonate, UV-resistant

Material color: white