

**B.E.G.****LUXOMAT®**

## PD4-S-C-SM Set

### 92442-92199-92376

Slave PIR motion detector with 360° coverage and a detection area of up to 40 x 5 m (250 m<sup>2</sup>), for hallways

#### Order data

Designation	Colour	Art.No
PD4-S-C-SM	white	92442
Wire basket BSK (Ø 200 x 90 mm)	white	92199
Surface mounting socket IP65 PD4-SM IP54	white	92376

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Ø 200 x 90 mm (92199)</b>
Power consumption:	approx. 0.2 W horizontal 360°
Detection area:	(Ceiling mounting) max. Ø 40 m across max. Ø 20 m towards
Range:	
Monitored area (tangential movement):	250 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection:	IP54 / Class II
Impact strength:	<b>IK09 (92199)</b>
Ambient temperature:	-25 °C to +50 °C <b>polycarbonate, UV-resistant + coated steel basket (92199)</b>
Housing:	
Material color:	white mat, similar to RAL9010
Pulse interval:	2 or 9 sec

## Product information

Set : PD4-S-C-SM + Wire basket BSK (Ø 200 x 90 mm) white + Surface mounting socket IP65 PD4-SM IP54 white

Slave device detector designed for corridors

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please see the respective master device.

There are markings to ensure correct alignment during installation




## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD4-S-C-SM**  
Art.No: 92442

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Ø 101 x 76 mm  
Power consumption: approx. 0.2 W



**Wire basket BSK (Ø 200 x 90 mm)**  
Art.No: 92199

Dimensions: Ø 200 x 90 mm  
Impact strength: IK09  
Housing: coated steel basket



**Surface mounting socket IP65 PD4-SM IP54**  
Art.No: 92376

Dimensions: Ø 115 x 70 mm  
Degree / class of protection: IP65  
Impact strength: IK07