

**B.E.G.**

**LUXOMAT®**



## PD4-S-C-SM Set 92442-92441

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **Ø 101 x 76 mm + 130 x 100 x 53 mm (92441)**
- Power consumption: approx. 0.2 W

### Order data

Designation	Colour	Art.No
PD4-S-C-SM	white	92442
Wall holder PD4-SM	white	92441

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Ø 101 x 76 mm + 130 x 100 x 53 mm (92441)</b>
Power consumption:	approx. 0.2 W horizontal 360°
Detection area:	(Ceiling mounting) max. Ø 40 m across
Range:	max. Ø 20 m towards
Monitored area (tangential movement):	250 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2.4 m / 2.6 m / 2.5 m
Degree / class of protection:	IP54 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Pulse interval:	2 or 9 sec

## Product information

Set : PD4-S-C-SM + Wall holder PD4-SM white

Slave device detector designed for corridors

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement  
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.

There are markings to ensure correct alignment during  
installation




## Set items

To receive the bundle according to the technical specification, please order the items listed.



**PD4-S-C-SM**  
Art.No: 92442

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Ø 101 x 76 mm  
Power consumption: approx. 0.2 W



**Wall holder PD4-SM**  
Art.No: 92441

Dimensions: 130 x 100 x 53 mm  
Housing: polycarbonate, UV-resistant  
Material color: white