

**B.E.G.****LUXOMAT®**

## PD4-S-DAA4G-SM Set 92759-92467-92441

- Voltage: 22 V DC via DALI Bus
- Dimensions: **Ø 164 x 143 mm (92467)**  
+ **130 x 100 x 53 mm (92441)**
- Detection area: horizontal 360° (Ceiling mounting)

### Order data

Designation	Colour	Art.No
PD4-S-DAA4G-SM	white	92759
Wire basket BSK (Ø 164 x 143 mm)	white	92467
Wall holder PD4-SM	white	92441

## Technical data

Voltage:	22 V DC via DALI Bus
Dimensions:	<b>Ø 164 x 143 mm (92467) + 130 x 100 x 53 mm (92441)</b>
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards seated
Range:	max. Ø 6.4 m seated
Monitored area (tangential movement):	450 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	IP54 / Class II
Impact strength:	<b>IK09 (92467)</b>
Ambient temperature:	-25 °C to +50 °C
Housing:	<b>polycarbonate, UV-resistant + coated steel basket (92467)</b>
Material color:	white mat, similar to RAL9010
up to 4 slave devices in combination with one PD4-M-DAA4G	
Pulse interval:	30 sec (in test mode 2 sec during 3 min)

## Product information

Set : PD4-S-DAA4G-SM + Wire basket BSK (Ø 164 x 143 mm) white + Wall holder PD4-SM white

DALI bus operated slave device

For extension of the detection area of a master device PD4-M-DAA4G / PD4-M-HCL

Trigger pulse to master device upon detected movement independent of the ambient light level

Automatic test mode via master device

Plug & Play - no parameterisation required

Easy to mount

False ceiling or surface mount version available



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD4-S-DAA4G-SM**

Art.No: 92759


Voltage: 22 V DC via DALI Bus  
Dimensions: Ø 103 x 76 mm  
Detection area: horizontal 360° (Ceiling mounting)



### **Wire basket BSK (Ø 164 x 143 mm)**

Art.No: 92467

Dimensions: Ø 164 x 143 mm  
Impact strength: IK09  
Housing: coated steel basket



### **Wall holder PD4-SM**

Art.No: 92441

Dimensions: 130 x 100 x 53 mm  
Housing: polycarbonate, UV-resistant  
Material color: white