

B.E.G.

LUXOMAT®



PD4-S-SM Set 92142-92441

Slave PIR motion detector with 360° coverage
and a range of up to Ø24m (450 m²)

Order data

| Designation | Colour | Art.No |
|--------------------|--------|--------|
| PD4-S-SM | white | 92142 |
| Wall holder PD4-SM | white | 92441 |

Technical data

| | |
|---|---|
| Voltage: | 110 - 240 V AC 50 / 60 Hz |
| Dimensions: | Ø 101 x 76 mm + 130 x 100 x 53 mm (92441) |
| Power consumption: | approx. 0.2 W |
| Detection area: | horizontal 360° (Ceiling mounting) max. Ø 24 m across |
| Range: | max. Ø 8 m towards max. Ø 6.4 m seated |
| Monitored area (tangential movement): | 450 m ² / 2.5 m mounting height |
| Mounting height min./max./recommended: | 2 m / 10 m / 2.5 m |
| Degree / class of protection: | IP54 / Class II |
| Impact strength: | IK04 |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | white mat, similar to RAL9010 |
| Pulse interval: | 2 or 9 sec |

Product information

Set : PD4-S-SM + Wall holder PD4-SM white

Slave device detector with extended detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.




PD4-S-SM

Art.No: 92142

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 101 x 76 mm

Power consumption: approx. 0.2 W



Wall holder PD4-SM

Art.No: 92441

Dimensions: 130 x 100 x 53 mm

Housing: polycarbonate, UV-resistant

Material color: white