

# B.E.G. LUXOMAT® net



## PD4N-CAS Set 93474-93786-92199

CASAMBI-compatible PIR motion sensor with 360° detection and a range of up to Ø24m (450 m<sup>2</sup>)

### Order data

Designation	Colour	Art.No
PD4N-CAS	white	93474
SM socle mounting set IP54 PD4N H	anthracite	93786
Wire basket BSK (Ø 200 x 90 mm)	white	92199

## Technical data

Voltage:	230 V AC ±10% 50 Hz
Dimensions:	<b>Ø 200 x 90 mm (92199)</b>
Settings:	Casambi App
Power consumption:	0.5 W
Detection area:	horizontal 360° oval (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	<b>IP54 (93786)</b>
Impact strength:	<b>IK09 (92199)</b>
Ambient temperature:	-5 °C to +45 °C <b>polycarbonate, UV-resistant + coated steel basket (92199)</b>
Housing:	<b>anthracite, similar to RAL7016 (93786)</b>
Material color:	
Number of PIR sensors:	4
<b>Channel 1 (lighting control)</b>	
Follow-up time:	1 sec - 60 min
Brightness set value:	1 - 4000 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD4N-CAS + SM socle mounting set IP54 PD4N  
H anthracite, similar to RAL7016 + Wire basket BSK  
(Ø 200 x 90 mm) white

Casambi-enabled occupancy detector

Bright LED indication for commissioning

Mixed light measurement with internal and external light  
sensor

Weighting between internal and external light sensor can be  
adapted to suit the application

Adjustment of the reflection factor and input of the luminosity  
for the display of the actual luminosity in the app

Extension of the detection area with additional B.E.G. Casambi  
devices possible

Individual adaption of detection sensitivity for each PIR sensor

Detection area can be restricted with blinds

Functions adjustable via Casambi app

Including pre-assembled spring clamp with strain relief and  
contact protection cap for recessed ceiling mounting

Accessory for surface mounting available

Accessories for wall mounting optionally available

Further accessories for colour matching optionally available



# CASAMBI



## Set items

To receive the bundle according to the technical specification, please order the items listed.




**PD4N-CAS**  
Art.No: 93474

Voltage: 230 V AC  $\pm 10\%$  50 Hz  
Dimensions:  $\varnothing 106 \times 95$  mm  
Settings: Casambi App



**SM socle mounting set IP54 PD4N H**  
Art.No: 93786

Dimensions:  $\varnothing 110 \times 45$  mm  
Degree / class of protection: IP54  
Material color: anthracite, similar to  
RAL7016



**Wire basket BSK ( $\varnothing 200 \times 90$  mm)**  
Art.No: 92199

Dimensions:  $\varnothing 200 \times 90$  mm  
Impact strength: IK09  
Housing: coated steel basket