

B.E.G.**LUXOMAT®**

PD4N-S Set

93241-92199-93786-93
073

Slave PIR motion detector with 360° coverage
and a range of up to Ø24m (450 m²)

Order data

Designation	Colour	Art.No
PD4N-S	white	93241
Wire basket BSK (Ø 200 x 90 mm)	white	92199
SM socle mounting set IP54 PD4N H	anthracite	93786
Corridor lens PD4N type A	white	93073

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 200 x 90 mm (92199) + Ø 110 x 45 mm (93786)
Power consumption:	approx. 0.2 W
Detection area:	horizontal 360° (Ceiling mounting) (93073) max. Ø 40 m across max. Ø 20 m towards (93073)
Range:	250 m² / 2.5 m mounting height (93073)
Monitored area (tangential movement):	2.4 m / 2.6 m / 2.5 m (93073)
Mounting height min./max./recommended:	IP54 (93786)
Degree / class of protection:	IK09 (92199)
Impact strength:	-25 °C to +50 °C
Ambient temperature:	polycarbonate, UV-resistant + coated steel basket (92199)
Housing:	white, similar to RAL9010 (93073)
Material color:	2 or 9 sec
Pulse interval:	

Product information

Set : PD4N-S + Wire basket BSK (Ø 200 x 90 mm)
white + SM socle mounting set IP54 PD4N H
anthracite, similar to RAL7016 + Corridor lens PD4N
type A white, similar to RAL9010

Slave device detector with extended detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.




PD4N-S

Art.No: 93241

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 106 x 92 mm

Power consumption: approx. 0.2 W



Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm

Impact strength: IK09

Housing: coated steel basket



SM socle mounting set IP54 PD4N H

Art.No: 93786

Dimensions: Ø 110 x 45 mm

Degree / class of protection: IP54

Material color: anthracite, similar to RAL7016



Corridor lens PD4N type A

Art.No: 93073

Detection area: horizontal 360° (Ceiling mounting)

Range: max. Ø 40 m across

max. Ø 20 m towards

Monitored area (tangential movement): 250 m² / 2.5 m mounting height