

**B.E.G.****LUXOMAT®**

## PD4N-S Set

# 93241-92199-93788

Slave PIR motion detector with 360° coverage and a range of up to Ø24m (450 m²)

### Order data

Designation	Colour	Art.No
PD4N-S	white	93241
Wire basket BSK (Ø 200 x 90 mm)	white	92199
SM socle mounting set IP54 PD4N H	black	93788

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Ø 200 x 90 mm (92199) + Ø 110 x 45 mm (93788)</b>
Power consumption:	approx. 0.2 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across max. Ø 8 m towards max. Ø 6.4 m seated
Range:	
Monitored area (tangential movement):	450 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	<b>IP54 (93788)</b>
Impact strength:	<b>IK09 (92199)</b>
Ambient temperature:	-25 °C to +50 °C
Housing:	<b>polycarbonate, UV-resistant + coated steel basket (92199)</b>
Material color:	<b>black, similar to RAL9005 (93788)</b>
Pulse interval:	2 or 9 sec

## Product information

Set : PD4N-S + Wire basket BSK (Ø 200 x 90 mm)  
white + SM socle mounting set IP54 PD4N H black,  
similar to RAL9005

Slave device detector with extended detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement  
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please  
see the respective master device.



## Set items


To receive the bundle according to the technical specification, please order the items listed.



### PD4N-S

Art.No: 93241

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Ø 106 x 92 mm  
Power consumption: approx. 0.2 W



### Wire basket BSK (Ø 200 x 90 mm)

Art.No: 92199

Dimensions: Ø 200 x 90 mm  
Impact strength: IK09  
Housing: coated steel basket



### SM socle mounting set IP54 PD4N H

Art.No: 93788

Dimensions: Ø 110 x 45 mm  
Degree / class of protection: IP54  
Material color: black, similar to RAL9005