

B.E.G.**LUXOMAT®**

PD4N-S Set 93241-93073

Slave PIR motion detector with 360° coverage
and a range of up to Ø24m (450 m²)

Order data

| Designation | Colour | Art.No |
|---------------------------|--------|--------|
| PD4N-S | white | 93241 |
| Corridor lens PD4N type A | white | 93073 |

Technical data

| | |
|---|--|
| Voltage: | 110 – 240 V AC 50 / 60 Hz |
| Dimensions: | Ø 106 x 92 mm |
| Power consumption: | approx. 0.2 W |
| Detection area: | horizontal 360° (Ceiling mounting) (93073) max. Ø 40 m across max. Ø 20 m towards (93073) 250 m² / 2.5 m mounting height (93073) |
| Range: | 2.4 m / 2.6 m / 2.5 m (93073) |
| Monitored area (tangential movement): | |
| Mounting height min./max./recommended: | 2.4 m / 2.6 m / 2.5 m (93073) |
| Degree / class of protection: | IP20 / Class II |
| Impact strength: | IK04 |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | white, similar to RAL9010 (93073) |
| Pulse interval: | 2 or 9 sec |

Product information

Set : PD4N-S + Corridor lens PD4N type A white,
similar to RAL9010

Slave device detector with extended detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement
independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please
see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-S

Art.No: 93241

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 106 x 92 mm

Power consumption: approx. 0.2 W



Corridor lens PD4N type A

Art.No: 93073

Detection area: horizontal 360° (Ceiling mounting)

Range: max. Ø 40 m across

max. Ø 20 m towards

Monitored area (tangential movement): 250 m² / 2.5 m mounting height