

B.E.G.**LUXOMAT®**

PD4N-S Set 93241-93733

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: Ø 106 x 92 mm
- Power consumption: approx. 0.2 W

Order data

Designation	Colour	Art.No
PD4N-S	white	93241
lens PD4N, Cover ring	black	93733

Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	Ø 106 x 92 mm
Power consumption:	approx. 0.2 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 24 m across
Range:	max. Ø 8 m towards max. Ø 6.4 m seated
Monitored area (tangential movement):	450 m ² / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 10 m / 2.5 m
Degree / class of protection:	IP20 / Class II
Impact strength:	IK04
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	black mat, similar to RAL9005 (93733)
Pulse interval:	2 or 9 sec

Product information

Set : PD4N-S + lens PD4N, Cover ring black mat, similar to RAL9005

Slave device detector with extended detection area

For extending the detection area of a Master device

Trigger pulse to master device upon detected movement independent of the ambient light level

Compatible with 230 V devices. Concerning exceptions please see the respective master device.



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD4N-S

Art.No: 93241

Voltage: 110 – 240 V AC 50 / 60 Hz

Dimensions: Ø 106 x 92 mm

Power consumption: approx. 0.2 W

lens PD4N, Cover ring

Art.No: 93733

Detection area: horizontal 360° (Ceiling mounting)

Range: max. Ø 24 m across

max. Ø 8 m towards

max. Ø 6.4 m seated

Monitored area (tangential movement): 450 m² / 2.5 m mounting height