

**B.E.G.****LUXOMAT®**

## PD9-M-1C-FC Set 92900-92958-92993

- Voltage: 110 - 240 V AC 50 / 60 Hz
- Dimensions: **Sensor head: Ø 45 x 28 mm, Power supply: 165 x 24 x 24 mm + 45 x 45 x 2.6 mm (92993)**
- Power consumption: approx. 0.5 W

### Areas of application

- entrance halls
- small offices
- corridors/hallways

### Order data

Designation	Colour	Art.No
PD9-M-1C-FC	white	92900
Cover IP65 for Sensor head PD9	transparent	92958
Square design frame PD9-FC	pure white	92993

## Technical data

Voltage:	110 - 240 V AC 50 / 60 Hz
Dimensions:	<b>Sensor head: Ø 45 x 28 mm, Power supply: 165 x 24 x 24 mm + 45 x 45 x 2.6 mm (92993)</b>
Power consumption:	approx. 0.5 W
Detection area:	horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated
Range:	78 m <sup>2</sup> / 2.5 m mounting height
Monitored area (tangential movement):	2 m / 5 m / 2.5 m
Mounting height min./max./recommended:	<b>IP20 / Class II + IP65 (92958)</b>
Degree / class of protection:	IK03
Impact strength:	-25 °C to +50 °C
Ambient temperature:	polycarbonate, UV-resistant
Housing:	<b>pure white mat, similar to RAL9010 (92993)</b>
Material color:	45 cm, screened
Cable length:	

### Channel 1 (lighting control)

Switching power:	2300 W, cos $\varphi$ = 1 1150 VA, cos $\varphi$ = 0.5 800 W LED max. inrush current $I_p$ (20 ms) = 165 A max. inrush current $I_p$ (200 $\mu$ s) = 800 A 1x $\mu$ -contact, NO contact with tungsten pre- make contact
Type of contact (k):	5 min - 30 min, Pulse
Follow-up time:	20 - 1000 Lux
Switch-on threshold:	Mixed light measuring
Light measuring:	

## Product information

Set : PD9-M-1C-FC + Cover IP65 for Sensor head PD9  
transparent + Square design frame PD9-FC pure  
white mat, similar to RAL9010

Mini-occupancy detector

One channel for light switching

Version as master device

Detection area can be extended by using slave devices

### Easy operation with remote control (required)

Manual switching via push-button possible

Power supply passes through the hole in the ceiling for the  
detector (34 mm Ø)

Spring clips for quick and easy installation in suspended  
ceilings and light fittings

Includes 45 mm cover ring and blinds

Factory settings 10 min and 500 lux



## Set items

To receive the bundle according to the technical specification, please order the items listed.




**PD9-M-1C-FC**  
Art.No: 92900

Voltage: 110 – 240 V AC 50 / 60 Hz  
Dimensions: Sensor head: Ø 45 x 28 mm,  
Power supply: 165 x 24 x 24 mm  
Power consumption: approx. 0.5 W



**Cover IP65 for Sensor head  
PD9**  
Art.No: 92958

Degree / class of protection: IP65  
Housing: UV-resistant  
Material color: transparent



**Square design frame PD9-FC**  
Art.No: 92993

Dimensions: 45 x 45 x 2.6 mm  
Housing: polycarbonate, UV-resistant  
Material color: pure white mat,  
similar to RAL9010