

**B.E.G.****LUXOMAT®**

## PD9-M-1C-SDB-IP65-FC Set 92912-92915

- Voltage: 230 V AC  $\pm 10\%$  50 Hz
- Dimensions: Sensor head:  $\varnothing 36 \times 28$  mm,  
Power supply:  $154 \times 40 \times 26$  mm
- Power consumption: 2.2 W

### Areas of application

- entrance halls
- plumbed rooms/bathrooms

### Order data

Designation	Colour	Art.No
PD9-M-1C-SDB-IP65-FC	white	92912
PD9-S-SDB-FC	white	92915

## Technical data

Voltage:	230 V AC $\pm 10\%$ 50 Hz
Dimensions:	Sensor head: $\varnothing$ 36 x 28 mm, Power supply: 154 x 40 x 26 mm
Power consumption:	2.2 W
Detection area:	horizontal 360° (Ceiling mounting) max. $\varnothing$ 10 m across
Range:	max. $\varnothing$ 6 m towards max. $\varnothing$ 4 m seated
Monitored area (tangential movement):	78 m <sup>2</sup> / 2.5 m mounting height
Mounting height min./max./recommended:	2 m / 5 m / 2.5 m
Degree / class of protection:	IP65 / Class III
Impact strength:	IK03
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Cable length:	350 cm
<b>Channel 1 (lighting control, potential-free (dry))</b>	
Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 400 W LED max. inrush current $I_p$ (20 ms) = 80 A
Type of contact (k):	1x $\mu$ -contact, dry NO contact
Follow-up time:	15 sec - 30 min, Pulse
Switch-on threshold:	20 - 1500 Lux
Light measuring:	Mixed light measuring

## Product information

Set : PD9-M-1C-SDB-IP65-FC + PD9-S-SDB-FC white,  
similar to RAL9010

Mini-occupancy detector designed for high-humidity locations

One potential-free (dry) switching contact

Version as master device

One additional Slave device sensor can be directly connected


Additional functions can be set up using the optional remote  
control.

Mounting in closed ceilings is not possible

Spring clips for quick and easy installation in suspended  
ceilings and light fittings



power supply



sensor head



## Set items

To receive the bundle according to the technical specification, please order the items listed.



### **PD9-M-1C-SDB-IP65-FC**

Art.No: 92912

Voltage: 230 V AC  $\pm 10\%$  50 Hz

Dimensions: Sensor head:  $\varnothing$  36 x 28 mm, Power supply: 154 x 40 x 26 mm

Power consumption: 2.2 W



### **PD9-S-SDB-FC**

Art.No: 92915

Dimensions:  $\varnothing$  36 x 28 mm

Detection area: horizontal 360° (Ceiling mounting)

Range: max.  $\varnothing$  10 m across

max.  $\varnothing$  6 m towards

max.  $\varnothing$  4 m seated