

B.E.G.

LUXOMAT®



PD9-SH-24V-2W Set 93213-92238

- Voltage: 24 V DC
- Dimensions: Ø 45 x 28 mm
- Detection area: horizontal 360° (Ceiling mounting)

Order data

| Designation | Colour | Art.No |
|------------------------|--------|--------|
| PD9-SH-24V-2W | white | 93213 |
| Cover ring PD9 Ø 36 mm | white | 92238 |

Technical data

| | |
|---|---|
| Voltage: | 24 V DC |
| Dimensions: | Ø 45 x 28 mm |
| Detection area: | horizontal 360° (Ceiling mounting) max. Ø 10 m across max. Ø 6 m towards max. Ø 4 m seated |
| Range: | |
| Monitored area (tangential movement): | 78 m ² / 2.5 m mounting height |
| Mounting height min./max./recommended: | 2 m / 5 m / 2.5 m |
| Degree / class of protection: | IP20 / Class II |
| Impact strength: | IK03 |
| Ambient temperature: | -5 °C to +45 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | white glossy (92238) |
| Cable length: | 350 mm |
| Switching power: | 24 V DC / 100mA Pulse |

Product information

Set : PD9-SH-24V-2W + Cover ring PD9 Ø 36 mm
white glossy

motion detector

For integration into building automation systems

Output 24V DC / 100 mA



Set items

To receive the bundle according to the technical specification, please order the items listed.



PD9-SH-24V-2W

Art.No: 93213

Voltage: 24 V DC

Dimensions: Ø 45 x 28 mm

Detection area: horizontal 360° (Ceiling mounting)



Cover ring PD9 Ø 36 mm

Art.No: 92238

Dimensions: Ø 36 mm

Housing: polycarbonate, UV-resistant

Material color: white glossy