B.E.G. LUXOMAT® net



RM-DALI-LINK-1C-REG

Prod.No. 93807 EAN: 4007529938070

DIN-rail DALI relay module with 1 switching channel

High-output and potential-free contact for loads with high inrush current

Integrated application controller with different operating modes

Order data

Designation	Colour	Art.No
RM-DALI-LINK-1C-REG		93807

Technical data

Voltage:	via DALI Bus, max. 22.5 V DC
Dimensions:	85 x 18 x 63 mm (1 TE)
Settings:	PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android)
Typ. power input:	10 mA
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white
Relay	
Switching power:	3000 W, cos φ = 1 1500 VA, cos φ = 0.5
Type of contact (k):	µ-contact, NO contact
Follow-up time:	1 min – 150 min (Cut-off and HVAC mode only)
Switch-on delay:	1 min – 150 min (HVAC mode only)

Product information

DIN-rail DALI relay module with 1 switching channel


High-output and potential-free contact for loads with high inrush current


Integrated application controller with different operating modes

Operating modes: Standard, Cut-off, HVAC, Impulse, Alarm

DIP- and HEX-switch for quick commissioning with basic functionality

Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALI-LINK


44
85.5
45.4
18
58.3


L
N
PS-DALI-LINK
L
N
DA+
DA-
PS-DALI-LINK
(option)
L
N
DA+
DA-
L
N
DA
DA
EVG / BE / EB
R1
R1
DA
DA
RM-DALI-LINK
-1C-REG
DA
DA
other DALI-LINK
control devices
DA
DA
PBM-DALI-LINK
-4W-BLE