



RM-DALI-SYS-1C-REG

Prod.No. 92849 EAN: 4007529928491

- Voltage: via DALI Bus, max. 22 V DC
- Dimensions: 85 x 18 x 63 mm (1 TE)
- Settings: via DIP switch, HEX switch, B.E.G. BLE App, B.E.G. PC Tools, B.E.G. DALI Router

Order data

| Designation | Colour | Art.No |
|--------------------|--------|--------|
| RM-DALI-SYS-1C-REG | | 92849 |

Technical data

| | |
|-------------------------------|---|
| Voltage: | via DALI Bus, max. 22 V DC |
| Dimensions: | 85 x 18 x 63 mm (1 TE) via DIP switch, HEX switch, B.E.G. BLE App, B.E.G. PC Tools, B.E.G. DALI Router |
| Settings: | |
| Typ. power input: | 10 mA |
| Degree / class of protection: | IP20 / Class II |
| Ambient temperature: | -25 °C to +50 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | white |
| Relay | |
| Switching power: | 3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$ |
| Type of contact (k): | μ -contact, NO contact |
| Follow-up time: | 1 min - 150 min (Cut-off and HVAC mode only) |
| Switch-on delay: | 1 min - 150 min (HVAC mode only) |

Product information

DIN-rail DALI relay module with 1 switching channel

High-output and potential-free contact for loads with high inrush current

Seamless integration in B.E.G. LUXOMAT®net DALI-SYS

Integrated application controller with different operating modes

Operating modes: Standard, Cut-off, HVAC, Impulse, Alarm

DIP- and HEX-switch for quick commissioning with basic functionality

Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALI-SYS



