



Einsatz	Produkt	Bereich	Schalten	DALI Kompakt	BMS DALI-2	DALI-LINK	DALI-SYS	CASAMBI	Vernetzt	SLAVE
Kleines Büro > 13m²	PD2(N)	Ø 10 m	M-1C AP 92550 DE 92565 UP 92555	BROADCAST M-DACO DALI-2* DE 93452 M-DACO-1C DALI-2* DE 93455	BMS DALI-2 DE 93543 UP 93544		DALI-SYS DE 93369 UP 93368	CAS DE 93477 CAS DALI-2 DE 93477	KNXs-ST* DE 93510 UP 93511 KNXs-DX* DE 93512 UP 93513	S AP 92152 DE 92166 UP 92156
			M-2C AP 92150 DE 92165 UP 92155							
			M-1C DE 92900	BROADCAST M-DACO DALI-2 DE 93470					KNXs-DX DE 93520	S DE 92905
	PD9	Ø 10 m	M-2C DE 92976							
			M-1C DE 92583	BROADCAST M-DACO DALI-2 DE 93459	BMS DALI-2 DE 93542	DALI-LINK DE 93068	DALI-SYS DE 92731		KNXs-ST DE 93522 KNXs-DX DE 93523	S DE 92593
	PD11	Ø 9 m								
Großes Büro > 32m²	PD4(N)	Ø 24 m	M-1C AP 92580 DE 92585 UP 92575	BROADCAST M-DACO DALI-2* DE 93460 M-DACO-1C DALI-2* DE 93463	BMS DALI-2 DE 93546	DALI-LINK DE 93377	DALI-SYS DE 93340	CAS DE 93474 CAS DALI-2 DE 93473	KNXs-ST* DE 93514 UP 93515 KNXs-DX* DE 93516 UP 93517	S AP 92142 DE 92254 UP 92163
			M-2C AP 92140 DE 92148 UP 92255	MULTICAST M-HCL2 AP 93485 DE 93484						
			M-3C-TRIO AP 92740 DE 92745	MULTICAST M-DAA4G AP 92743 DE 92591 M-HCL2 AP 93485 DE 93484		DALI-LINK DE 93377			KNXs-ST* DE 93514 UP 93515	S AP 92142 DE 92254 UP 92163
Durchgangs- bereich, Flure	PD4(N)-K	max. 40 m	M-1C AP 92587 DE 92586	BROADCAST M-DACO DALI-2* DE 93460 + 93073 M-DACO-1C DALI-2* DE 93463 + 93073	BMS DALI-2 DE 93546 + 93073	DALI-LINK DE 93377 + 93073	DALI-SYS DE 93340 + 93073	CAS DE 93474 + 93073 CAS DALI-2 DE 93473 + 93073	KNXs-ST* DE 93514 + 93073 UP 93515 + 93073 KNXs-DX* DE 93516 + 93073 UP 93517 + 93073	S AP 92442 DE 92444
			M-2C AP 92440 DE 92143 UP 92443							
Treppenhaus	Indoor 180	max. r=10m	1C AP 92190 UP 92186							
			R UP** 92623 UP 92665						KNXs-ST UP 93524 KNXs-DX UP 93525	
			TR UP** 92650 UP 92668							
			M-2C UP** 92136 UP 92661							
Industriehallen, Logistikhallen	PD4-GH	Ø 30 m	M-1C AP 92245	BROADCAST M-DACO-GH DALI-2 AP 93469	BMS DALI-2 AP 93545	DALI-LINK AP 93845	DALI-SYS AP 93345	CAS2 AP 93479 CAS2 DALI-2 AP 93478		S AP 92265
			M-1C AP 92580	BROADCAST M-DACO DALI-2* DE 93460				CAS DE 93474	KNXs-ST* UP 93515	S AP 92142
			M-2C AP 92140	M-DACO-1C DALI-2* DE 93463				CAS DALI-2 DE 93473	KNXs-DX* UP 93517	
Parkplatz, Parkhaus	RC-plus next N	max. 20m	130° □ 93321 230° □ 93331						230° KNXs-DX □ 93527	
Sporthallen	PD4(N)	Ø 24 m	M-1C AP 92580	BROADCAST M-DACO DALI-2* DE 93460	BMS DALI-2 DE 93546	DALI-LINK DE 93377	DALI-SYS DE 93340	CAS DE 93474 CAS DALI-2 DE 93473	KNXs-ST* DE 93514 UP 93515 KNXs-DX* DE 93516 UP 93517	
			M-2C AP 92140	M-DACO-1C DALI-2* DE 93463						
Reichweite 3-16 m	Aleum Glow	max. 16m	180° □ 93132							
Reichweite bis 12 m	LC-Click-N	max. 12m	140° □ 91001 200° □ 91002							
Reichweite bis 16 m	LC-plus	max. 16m	280° □ 91008				280° DALI-SYS □ 93308			
Reichweite bis 20 m	RC-plus next N	max. 20m	130° □ 93321 230° □ 93331 280° □ 93341						230° KNXs-DX □ 93527	




**PD2/PD2N, PD3/PD3N,
PD9/PICO**




PD4/PD4N




PD4-GH




PD4-K




PD4-DS




PD5N




PD9-GH




HF-MD1/HF-MD2




PD11




BL2




BL4




BL4-K




Indoor 180




Indoor 180N




Indoor 140-L




Indoor HF




LC-Mini 120




**LC-Click 140/
LC-Click-N 140**




**LC-Click 200/
LC-Click-N 200**




LC-plus 280




Aleum Glow



RC-plus next N 130



RC-plus next N 230



RC-plus next N 280

