



BIA-4-KNX REG

Prod.No. 90405 EAN: 4007529904051

- Voltage: via KNX BUS
- Dimensions: 60 x 18 x 90 mm (1 TE)
- Typ. power input: 5 mA

Order data

| Designation | Colour | Art.No |
|---------------|--------|--------|
| BIA-4-KNX REG | - | 90405 |

Technical data

| | |
|-------------------------------|--|
| Voltage: | via KNX BUS |
| Dimensions: | 60 x 18 x 90 mm (1 TE) |
| Typ. power input: | 5 mA |
| Degree / class of protection: | IP20 / Class II |
| Ambient temperature: | -5 °C to +45 °C |
| Housing: | polycarbonate, UV-resistant |
| Material color: | - |
| KNX TP 256: | Yes |
| Connections and wires: | 1 x Bus line: EIB/KNX bus terminal (black/red) |
| | 6 x Screw terminals |
| | 0.34 ... 2.5 mm ² rigid |
| | 0.34 ... 2.5 mm ² fine-wired |

Product information

Compact binary input with 4 channels for controlling luminaires, blinds, etc

The inputs can be controlled via conventional switches with an external voltage of 12 to 230 V

Use as a pulse counter is possible

Two push-buttons and three LEDs enable local operation and visualisation of the unit's status

In addition to the input channels, the unit contains 16 independent logic or time functions



