

**B.E.G.****LUXOMAT®**

## CdS-SM

Prod.No. 92369 EAN: 4007529923694

- Voltage: 110 – 240 V AC 50 / 60 Hz
- Dimensions: 42 x 80 x 96 mm
- Power consumption: < 0.5 W

### Order data

**Designation**  
CdS-SM

**Colour**  
white

**Art.No**  
92369

## Technical data

Voltage:	110 – 240 V AC 50 / 60 Hz
Dimensions:	42 x 80 x 96 mm
Power consumption:	< 0.5 W
Degree / class of protection:	IP54 / Class II
Impact strength:	IK01
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white
<b>Channel 1 (lighting control)</b>	
Switching power:	2300 W, $\cos \varphi = 1$ 1150 VA, $\cos \varphi = 0.5$ 300 W LED
Type of contact (k):	1x $\mu$ -contact, NO contact
Switch-on and -off delay:	1 s - 120 s
Switch-on threshold:	2 – 1000 Lux

## Product information

Photoelectric switch for automatically switching

Activation and deactivation delay with self-learning deactivation-light value

Integrated automatic function (10 Lux / 40 sec. activation / 120 sec. deactivation delay)

LED adjustment aid (without delay) for adjustment of the switch-on threshold

Light value and activation/deactivation delay may be set from the outside using the potentiometer

Double cable inlet from underneath possible

Wall and mast installation



