



## DA64-230/KNX REG

Prod.No. 93302 EAN: 4007529933020

- Voltage: 230 V AC -15/+10% 50 / 60 Hz
- Dimensions: 90 x 72 x 64 mm (4 TE)
- Typ. power input: 5.5 mA (KNX, typical)

### Order data

Designation	Colour	Art.No
DA64-230/KNX REG	-	93302

## Technical data

Voltage:	230 V AC -15/+10% 50 / 60 Hz
Dimensions:	90 x 72 x 64 mm (4 TE)
Typ. power input:	5.5 mA (KNX, typical)
Output voltage:	16 V DC (DALI, typical)
Power consumption:	0.9 – 6 W
Degree / class of protection:	IP20 / Class I
Ambient temperature:	-5 °C to +45 °C
Housing:	PA66
Material color:	-
KNX TP 256:	Yes
Nominal current:	160 mA
Nominal current (max.):	210 mA

## Product information

The gateway connects the KNX BUS with the DALI BUS (DALI BUS for controlling the illumination)

Each gateway is for controlling and dimming up to 64 electronic ballasts in 16 groups

Scenes module for controlling individual electronic ballasts

RGB and TW (DT8) support

Support of B.E.G. DALI-LINK multisensors, push-button modules, push-buttons and DALI relay modules

Commissioning via DCA

Broadcast command via integrated operating buttons

Support for DALI emergency luminaires

Compatible with most DALI drivers or DALI ballasts



