



DA64-230/KNX REG DALI-2

Prod.No. 93338 EAN: 4007529933389

- Voltage: 230 V AC -15/+10% 50 / 60 Hz
- Dimensions: 90 x 72 x 64 mm (4 TE)
- Typ. power input: 5.5 mA (KNX, typical)

Order data

| Designation | Colour | Art.No |
|-------------------------|--------|--------|
| DA64-230/KNX REG DALI-2 | - | 93338 |

Technical data

| | |
|-------------------------------|---------------------------------|
| Voltage: | 230 V AC -15/+10% 50 / 60 Hz |
| Dimensions: | 90 x 72 x 64 mm (4 TE) |
| Typ. power input: | 5.5 mA (KNX, typical) |
| Output voltage: | 16 V DC (DALI, typical) |
| Power consumption: | 0.9 – 6 W |
| Degree / class of protection: | IP20 / Class I |
| Ambient temperature: | -5 °C to +45 °C |
| Housing: | PA66 |
| Material color: | - |
| KNX TP 256: | Yes |
| Connections and wires: | KNX bus terminal black/red |
| Nominal current: | 160 mA |
| Nominal current (max.): | 250 mA |

Product information

KNX DALI gateway for controlling DALI lights

DALI-2 certified product

Each gateway is for controlling and dimming up to 64 electronic ballasts in 16 groups

Scenes module for controlling individual electronic ballasts

Support for RGB, Tunable White and Human Centric Lighting (DT8)

Support of B.E.G. DALI-LINK multisensors, push-button modules, push-buttons and DALI relay modules

Commissioning via DCA

Quick replacement of luminaires possible via DCA

Broadcast command with flashing function for simple commissioning of the lights via built-in operating buttons

Support for DALI emergency luminaires (DT1) with comprehensive diagnostic and test functions, suitable for connection to building management systems

Compatible with most DALI drivers or DALI ballasts



