



**L7**

Prod.No. 94451 EAN: 4007529944514

- Voltage: 230 V AC  $\pm 10\%$  50 / 60 Hz
- Dimensions:  $\varnothing$  300 x 110 mm
- Lamp: max. 23 W with bulb socket E 27

**Order data**

Designation	Colour	Art.No
L7	white	94451

## Technical data

Voltage:	230 V AC $\pm 10\%$ 50 / 60 Hz
Dimensions:	Ø 300 x 110 mm
Lamp:	max. 23 W with bulb socket E 27
Photobiological safety:	RG 0
Degree / class of protection:	IP40 / Class I
Impact strength:	94446=IK02, 94451=IK06
Ambient temperature:	-15 °C to +30 °C
Housing:	<b>L8:</b> acrylic glass <b>L7:</b> Polycarbonate
Material color:	white

## Product information

Round wall and ceiling light

Acrylic glass is suitable for all standard applications


Polycarbonate is appropriate for areas where greater impact resistance is required (e.g. schools, public buildings)

Ideally supplements the HF-L7 and HF-L8

Supply without lamp

### Application examples:

corridors, halls, staircases, storage rooms, cellars, toilets



h (m)	Ø (m)	E (lx)
1.0	3.7	27
2.0	7.4	7
3.0	11.0	3
4.0	14.7	2
5.0	18.4	1

