

**B.E.G.****LUXOMAT®**

## PD9-M-1C-SDB-IP65-GH-FC

Prod.No. 92931 EAN: 4007529929313

- Voltage: 230 V AC  $\pm 10\%$  50 Hz
- Dimensions: Sensor head:  $\varnothing 36 \times 40$  mm,  
Power supply:  $154 \times 38 \times 25$  mm
- Power consumption: 2.2 W

### Areas of application

- plumbed rooms/bathrooms
- sports halls/ storage rooms

### Order data

Designation	Colour	Art.No
PD9-M-1C-SDB-IP65-GH-FC	white	92931

### Accessories

Designation	Colour	Art.No
BLE-IR-Adapter	black	93067
IR-PD9	-	92201
IR-PD-Mini	-	92159
RC-Arc extinction kit	white	10880
Mini-RC-Arc extinction kit		10882

## Technical data

Voltage:	230 V AC $\pm 10\%$ 50 Hz
Dimensions:	Sensor head: $\varnothing$ 36 x 40 mm, Power supply: 154 x 38 x 25 mm
Power consumption:	2.2 W
Detection area:	horizontal 360° (Ceiling mounting)
Range:	max. $\varnothing$ 3.5 m across
Monitored area (tangential movement):	9 m <sup>2</sup> / 6 m mounting height
Mounting height min./max./recommended:	5 m / 10 m / 6 m
Degree / class of protection:	IP65 / Class III
Impact strength:	IK03
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white mat, similar to RAL9010
Cable length:	350 cm

### Channel 1 (lighting control, potential-free (dry))

Switching power:	2300 W, $\cos \varphi$ = 1 1150 VA, $\cos \varphi$ = 0.5 400 W LED max. inrush current $I_p$ (20 ms) = 80 A
Type of contact (k):	1x $\mu$ -contact, dry NO contact
Follow-up time:	15 sec – 30 min, Pulse
Switch-on threshold:	10 – 2000 Lux
Light measuring:	Mixed light measuring

## Product information

Mini-occupancy detector designed for high-humidity locations especially for large mounting heights

One potential-free (dry) switching contact

Version as master device

One additional Slave device sensor can be directly connected




Additional functions can be set up using the optional remote control.

Spring clips for quick and easy installation in suspended ceilings and light fittings

Includes 45 mm cover ring and blind

### Application examples:

plumbed rooms/bathrooms, sports halls/ storage rooms



## Accessories



### BLE-IR-Adapter

Art.No: 93067

Dimensions: 40 x 55 x 103 mm  
Material color: black  
Frequency: 2.4 GHz ISM band, GFSK 0.2 dBm + 5.3 dBi = 5.5 dBm



### RC-Arc extinction kit

Art.No: 10880

Voltage: 230 V AC  $\pm 10\%$   
Dimensions: 38 x 12 x 26 mm  
Degree / class of protection: IP20 / Class II



### IR-PD9

Art.No: 92201

Battery: 3.0 V Lithium CR2032 (inclusive)  
Dimensions: 80 x 60 x 8 mm  
Material color: -



### Mini-RC-Arc extinction kit

Art.No: 10882

Voltage: 230 V AC  $\pm 10\%$   
Dimensions: 50 x 23 x 8 mm  
Degree / class of protection: IP20 / Class II



### IR-PD-Mini

Art.No: 92159

Battery: 3.0 V Lithium CR2032 (inclusive)  
Dimensions: 57 x 35 x 7 mm  
Material color: -