



RM-DALI-SYS-1C-REG

Prod.No. 92849 EAN: 4007529928491

- Voltage: via DALI Bus, max. 22 V DC
- Dimensions: 85 x 18 x 63 mm (1 TE)
- Settings: via DIP switch, HEX switch, B.E.G. BLE App, B.E.G. PC Tools, B.E.G. DALI Router

Order data

Designation	Colour	Art.No
RM-DALI-SYS-1C-REG		92849

Technical data

Voltage:	via DALI Bus, max. 22 V DC
Dimensions:	85 x 18 x 63 mm (1 TE) via DIP switch, HEX switch, B.E.G. BLE App, B.E.G. PC Tools, B.E.G. DALI Router
Settings:	
Typ. power input:	10 mA
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white

Relay

Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$
Type of contact (k):	μ -contact, NO contact
Follow-up time:	1 min – 150 min (Cut-off and HVAC mode only)
Switch-on delay:	1 min – 150 min (HVAC mode only)

Product information

DIN-rail DALI relay module with 1 switching channel

High-output and potential-free contact for loads with high inrush current

Seamless integration in B.E.G. LUXOMAT®net DALI-SYS

Integrated application controller with different operating modes

Operating modes: Standard, Cut-off, HVAC, Impulse, Alarm

DIP- and HEX-switch for quick commissioning with basic functionality

Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALI-SYS



