



TS-ASTRO-4-BLE

Prod.No. 93161 EAN: 4007529931613

- Voltage: 230 V AC 50 / 60 Hz
- Dimensions: 45 x 36 x 58 mm (2 TE)
- Power consumption: 0.3 - 1 W

Order data

| Designation | Colour | Art.No |
|----------------|--------|--------|
| TS-ASTRO-4-BLE | grey | 93161 |

Technical data

| | |
|-------------------------------|---|
| Voltage: | 230 V AC 50 / 60 Hz |
| Dimensions: | 45 x 36 x 58 mm (2 TE) |
| Power consumption: | 0.3 – 1 W |
| Degree / class of protection: | acc. to DIN EN 60529 IP20 / Class II |
| Power back-up (at 20 °C): | approx. 10 years |
| Ambient temperature: | -30 °C to +55 °C |
| Housing: | self-extinguishing thermoplastic |
| Material color: | grey |
| | 3680 W / 16 A, $\cos \varphi = 1$ |
| Switching power: | 2300 VA, $\cos \varphi = 0.6$ 200 W LED max. inrush current I_p (20 ms) = 50 A |
| Type of contact (k): | μ -contact, Changeover contact, contact gap < 3 mm |
| Outputs: | 1 |

Product information

Digital ASTRO time switch for installation in branches

1 channel

Daily and weekly program

Night economy circuit and extra switching times

100 memory locations

Bluetooth integrated

Zero crossing switching

Free B.E.G. App offering a user-friendly navigation for installation on the Smartphone downloadable in the respective App store

Replaceable battery (CR2032)

Minimum interval 1 min.

Switching capacity 16 A per channel

Permanent by date / holiday function

Manual permanent mode

Manual override

Fully automatic daylight saving time

Elapsed time and pulse counter

Easy operation

Illuminated display

Security by PIN code



