



TS-ASTRO-5-BLE

Prod.No. 93162 EAN: 4007529931620

- Voltage: 230 V AC 50 / 60 Hz
- Dimensions: 45 x 36 x 58 mm (2 TE)
- Power consumption: 0.3 – 1 W

Order data

Designation	Colour	Art.No
TS-ASTRO-5-BLE	grey	93162

Technical data

Voltage:	230 V AC 50 / 60 Hz
Dimensions:	45 x 36 x 58 mm (2 TE)
Power consumption:	0.3 – 1 W
Degree / class of protection:	acc. to DIN EN 60529 IP20 / Class II
Power back-up (at 20 °C):	approx. 10 years
Ambient temperature:	-30 °C to +55 °C
Housing:	self-extinguishing thermoplastic
Material color:	grey
	3680 W / 16 A, $\cos \varphi = 1$
Switching power:	2300 VA, $\cos \varphi = 0.6$ 200 W LED max. inrush current I_p (20 ms) = 50 A
Type of contact (k):	μ -contact, Changeover contact, contact gap < 3 mm
Outputs:	2

Product information

Digital ASTRO time switch for installation in branches

2 channels

Daily and weekly program

Night economy circuit and extra switching times

100 memory locations

Bluetooth integrated

Zero crossing switching

Free B.E.G. App offering a user-friendly navigation for installation on the Smartphone downloadable in the respective App store

Replaceable battery (CR2032)

Minimum interval 1 min.

Switching capacity 16 A per channel

Permanent by date / holiday function

Manual permanent mode

Manual override

Fully automatic daylight saving time

Elapsed time and pulse counter

Easy operation

Illuminated display

Security by PIN code



